

SMARTLINE

Line Interactive UPS (0.5 to 3 KVA)



AN ISO 9001 & 14001 CERTIFIED COMPANY

The Standby Line Interactive UPS Systems from Uniline are Economical Datasaver and Manufactured with the Latest Power Conversion Techniques. Employed with excellent Line Filtering Devices PWM Technology used for Power Conversion with its Unique Single Transformer arrangement permits Lowest change over time, Greater System Efficiency, Compact Size and High Reliability.

Indeed, an Intelligent 4-in-1 standby UPS is just perfect for PCS, Pentium, Micro and Mini Computers, Peripherals, Biomedical Equipments etc.

SAILENT FEATURES :

- Very Wide Input Range.
- Cold Start Facility, can be started during Power failure.
- Input Filters for Line Noise and Spikes
- Overload, Short Circuit Protection
- RS 232 C Interface saves Data on Most Operative System. (Optional)



UNILINE ENERGY SYSTEMS PRIVATE LIMITED

SMARTLINE TECHNICAL SPECIFICATIONS



RATING		500 VA	625 VA	1000 VA	2000 VA
INPUT	Voltage	140 V AC to 280 V AC			
	Frequency	50 Hz ± 6%			
	DC Voltage	12 V	24 V		24 V / 48 V
OUTPUT	Voltage	220 V + 9 % (Mains Mode) 220 V + 5 % (Battery Mode)			
	Frequency	Same as Input (Under Mains Mode) 50 Hz ± 1 % (Under Battery Mode)			
BUILT - IN BATTERY (SMF)		1 × 12V 7AH			
EXTERNAL BATTERY		Charging Current Options Up To 20 Amps			
MAX. CHARGING VOLTAGE		13.8V	27.6V		27.6V / 55.2V
90% RECHARGE TIME		3 to 4 Hours			
EFFICIENCY		AC TO AC > DC TO AC > 80 %			
PROTECTIONS		Short Circuit	Electronic Shutdown		
		Overload	Electronic Shutdown		
		Low Battery	Electronic Shutdown		
INDICATIONS		500 VA to 15 KVA UPS	1 KVA to 2 KVA UPS		
		Load on AC	AC On		
		Load on DC	DC On		
		Over Load / LOW	Battery Level		
		Battery Trip	Load Level Graph		
COMMUNICATION PORT		DB - 9 Female / R S 232 C / USB PORT (Optional)			
ENVIRONMENT	Temperature	0° C to 45° C			
	Humidity	30 % to 95 %			
ACOUSTIC NOISE LEVEL		< 40 db at One Meter			

NOTE : EXTERNAL BATTERY MODEL UPS FOR 1 - 4 HRS. BACKUP TIME ARE ALSO AVAILABLE

*The above system are based on normal standards and can be customised as per specifications

Our Other Products :

- UNIPLUS (600 VA) • Green Line Series (Upto 6 KVA)
- Modular Series (15KVA to 20 KVA) • Maxi Power IGBT On Line UPS System (Upto 25 KVA)
- D Series UPS (60KVA to 300 KVA) • GigaPower (Tripower) IGBT Online UPS upto 500 KVA



UNILINE ENERGY SYSTEMS (P) LTD.

Uniline House, 198 / 23, Ramesh Market, East Of Kailash,
New Delhi - 110 065
Tel.: 011- 4666 1111 / 2646 9031 / 2646 9108
Fax : 011 - 2648 1469
E mail : uniline@uniline.in
www.unilineindia.com

AUTHORISED DEALER :

ALL SPECIFICATION ARE SUBJECT TO CHANGE WITHOUT NOTICE DUE TO CONTINUOUS TECHNOLOGY UPGRADATION.
ALL TRADE MARKS LIKE NOVELL, UNIX, WINDOWS, DOS ARE THE PROPERTY OF THEIR RESPECTIVE OWNERS

Branch Offices : • Ahmedabad • Bangalore • Bhopal • Bhubaneswar • Chandigarh • Chennai • Dehradun • Jaipur
• Kanpur • Kolkata • Lucknow • Mumbai • Patna • Raipur • Ranchi • Secunderabad